

TBE-440 TIG Brush Specifications



Model Designation	TIG Brush® TBE-440
Market Location	All regions except AUS/NZ
Feature	Details
Case Design	440 Series Injection Moulded IP65
Case Material	PC/ABS
Case Colour	Grey
Dimensions	245W x 190D x 370H
Weight (kg)	11kg
Mains Voltage	110/220 volts +5%/-10%, single phase
Input Current	Up to 7 amps
Operating Environment	-30°C to +45°C
Duty Cycle	Rated for continuous use at an ambient temperature of 30 degrees Centigrade, on any Grade and Power setting.
Application Selection	Rotary Switch
Applications	Sleep 0V Single Brush 11V PROPEL™ / Wide 14V
Mode Selection	Rotary Switch
Modes Available	Turbo Clean Polish / Etch Mark
Power Supply	Dynamic Power Transfer – 300VA
Maximum Operating Output Current	50 amps
Overload Control	Smart Circuit
Cables (2)	Red PVC insulated 4 metre with Handle Black PVC insulated 4 metre with Clamp
Brush Connection	Threaded M6
Maximum Brush size	Dual
Standards Compliance	C-Tick N22274
<p><i>Note: Ensitech reserves the right to update product specifications at any time without notice.</i></p>	

Ensitech Pty Ltd ABN 92 144 914 401
 1/144 Old Bathurst Rd, Emu Plains NSW 2750 Australia
 PO Box 179 Springwood NSW 2777 Australia
 T +61 2 4735 7700 F +61 2 4735 7744
www.tigbrush.com

