

TBE-700 TIG Brush Specifications



Model Designation	TIG Brush® TBE-700
Market Location	All regions except AUS/NZ
Feature	Details
Case Design	700 Series Injection Moulded IP65
Case Material	PC/ABS
Case Colour	Purple
Dimensions	245W x 190D x 370H
Weight (kg)	12kg
Mains Voltage	110/220 volts +5%/-10%, single phase
Input Current	Up to 8 amps
Operating Environment	-30°C to +45°C
Duty Cycle	Rated for continuous use at an ambient temperature of 30 degrees Centigrade, on any Grade and Power setting
Application Selection	Rotary Switch
Applications	Sleep 0V Narrow / Single Brush 13.5V PROPEL™ / Wide 18V
Mode Selection	Rotary Switch
Modes Available	Turbo Clean Polish / Etch Mark
Power Supply	Dynamic Power Transfer – 700VA
Maximum Operating Output Current	90 amps
Overload Control	Smart Circuit
Cables (2)	Red PVC insulated 6 metre with Handle Black PVC insulated 6 metre with Clamp
Brush Connection	Threaded M6
Maximum Brush size	Quad
Standards Compliance	CE, C-Tick N22274
<p>Note: Ensitech reserves the right to update product specifications at any time without notice.</p>	